

## **HOSE COMPATIBILITY SPECIFICATION**

Part No	Primary Hose Applications *	Unicoil I.D.	HOSE Min O.D.	HOSE Max O.D.
UC14091	6.3mm (1/4") I.D. Fuel hose, Heater hose	13 mm	11 mm	13 mm
UC51691	7.9mm (5/16") I.D. Fuel, Heater & trans oil hoses	16 mm	14 mm	16 mm
UC38091	9.5mm (3/8") I.D. Heater hose, trans oil hose	18 mm	16 mm	18 mm
UC12091	13mm (1/2") I.D. Heater hose	21 mm	19 mm	21 mm
UC58091	16mm (5/8") I.D. Heater hose	24 mm	22 mm	24 mm
UC34091	19mm (3/4") I.D. Heater hose	28 mm	26 mm	28 mm
UC10091	25.4mm (1") I.D. Heater hose	36 mm	34 mm	36 mm

Hose matching guide: A snug fit with approximately 0.5 - 1mm clearance will provide best results

\* Primary hose applications are intended as a basic guide only. Unicoil products are compatible with oil, air, water and fuel hoses. Additional applications are possible, refer to hose Min and Max O.D.'s to match Unicoil with other hoses not listed here.











## **Instructions**



Slide the Unicoil to where the bend is required. Position the spine on the inside of the intended bend.



Press and bend the spine until the required bend angle is achieved.



Maximum bend angle is 90 Degrees



For best results create a gradual bend in the spine and avoid making a sharp bend